



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



UT132 SERIES

Palm Size Digital Multimeters

UT132C ■ UT132D



EN:61010-1

EN:61326-1



■ UT132C



■ UT132D

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT132C	UT132D
Model			
DC Voltage (V)	200mV/ 2000mV/ 20V/ 200V/ 250V	±(0.5%+2)	±(0.5%+2)
AC Voltage (V)	200V/ 250V	±(1.2%+3)	±(1.2%+3)
DC Current (A)	2000µA/ 20mA/ 200mA/ 10A	± (1%+2)	± (1%+2)
Resistance (Ω)	2000µA/ 200mA/ 10A		± (1%+2)
	200Ω/ 2000Ω/ 20KΩ/ 200KΩ/ 2000KΩ/ 20MΩ	±(1.2%+3)	
Capacitance (F)	200Ω/ 2000Ω/ 20KΩ/ 200KΩ/ 20MΩ		±(0.8%+5)
	20nF/ 2000nF/ 200µF		±(4%+3)
Temperature (°C)	-40 °C ~ 1000°C	±(1.0%+3)	
Features			
Display Count		1999	1999
Manual Range		✓	✓
Diode		✓	✓
Transistor		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	49mm × 18mm
Product Color	Red and Grey
Product Net Weight	200g
Product Size	72mm × 137mm × 35mm
Standard Accessories	UT132C-Battery , Test Lead , Multi-Purpose Socket, Point Contact Temperature Probe
	UT132D-Battery , Test Lead , Multi-Purpose Socket
Standard Individual Packing	Gift Box , English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm × 365mm × 290mm (0.057CBM Per Standard Carton)
Standard Carton Gross Weight	13.8 Kg