



HESTORE.HU


elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.



Please visit our website for pricing and availability at www.hestore.hu.

EC12 Series Specification


EC12E20-24P24C-SW	
Mechanical Characteristics	
ITEM	SPECIFICATION
Total Rotational Angle	360°
Rotational Torque	□ 20≈200gf.cm
Click pull-out Torque	□ 20≈150gf.cm
Shaft push-pull Strength	8.0kgf-8.0kgf Min at 8sec
Shaft Wobble Strength	0.7xL/30 mm P-P max L:shaft length
Number of Click	■ 24 clicks Step Angle:15° ±2°
Bushing-nut tightening strength	7.0kgf.cm Min
Shaft rotational gap	0.4mm Max
Shaft play in rotational wobble	5° Max
Electrical Characteristics	
ITEM	SPECIFICATION
Power rated	DC 5V, A、B lead 5mA Max, C lead 10mA Max
Output signal	A、B 2 signals
Resolution	■ 24 pulses/360°
Contact resistance between pins	1 Ω Max
Phase difference	T1、T2、T3、T4≥0.06°
Rotation noise	t1, t3≤3mS t2≤2mS
Insulation resistance	100MΩMin at DC 250V
Dielectric	1 minute at AC 300V
Endurance characteristics	
ITEM	SPECIFICATION
Rotational life	□ 30,000±200 cycles ≤100gf.cm □ 15,000±200 cycles ≥100gf.cm
Storage temperature range	-40℃≈+85℃
Operating temperature range	-30℃≈+80℃
Soldering characteristic	dipping in soldering≤206℃±5° ,within 3S solder by hand:≤300℃±5° ,within 3S




Shaft Shown in Full
C.C.W. Position



P.C.B MOUNTING DETAIL



CW →



← CCW

L	20 ✓	22.5	25
F	7 ✓	7	12

02				05			
01				04			
	DATE	REVISION	APPROVED	03			
							DRAWING NO:
			MODEL: EC12E20-24P24C-SW				
2016.12.10	2016.12.10	2016.12.10	SRPASSIVES				
DRAW	CHKD	APPD					