



HESTORE.HU


elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Carbon Film Resistor

SRPASSIVES



Specifications

POWER RATING	MAXIMUM WORKING VOLTAGE	MAXIMUM OVERLOAD VOLTAGE	DIMENSIONS(mm)				RESISTANCE RANGE
			L	D	H	d±0.02	
1/8W, 1/8W	200V	400V	3.2±0.2	1.8±0.2	28±2.0	0.43	STANDARD 1Ω-10MΩ
1/4WS	250V	500V	3.2±0.2	1.8±0.2	28±2.0	0.43	
1/4W	250V	500V	6.0±0.5	2.3±0.5	28±2.0	0.50	
1/2WS	350V	700V	6.0±0.5	2.3±0.5	28±2.0	0.50	
1/2W	350V	700V	9.0±0.5	3.2±0.5	26±2.0	0.60	
1WS	500V	1000V	9.0±0.5	3.2±0.5	26±2.0	0.60	
1W	500V	1000V	11.0±1.0	3.7±0.5	35±2.0	0.70	
1W	500V	1000V	11.0±1.0	4.2±0.5	25±2.0	0.70	
2WS	500V	1000V	11.0±1.0	4.2±0.5	35±3.0	0.70	
2W	500V	1000V	15.0±1.0	5.0±0.5	33±3.0	0.75	
3W	500V	1000V	17.0±1.0	6.0±0.5	38±3.0	0.75	

Electrical Specifications

Test Items	Condition			Spec	
Short Time Overload	2.5 times of RCWV for 5 secs.			±(2%+0.05 Ω)	
Load life	70°C at rated power 1.5hrs on;0.5 hr off for 1000hrs			±(5%+0.05 Ω)	
Dielectric Withstanding Voltage	Max Overload Voltage 1 Minute			±(0.5%+0.05 Ω)	
Temp. Cycling	-30°C / +85°C for 5 cycles			±(1%+0.05 Ω)	
Insulation Resistance	D.C. 500V			1000MΩ	
Moisture-proof Load Life	40°C 95% RH 1.5hrs on / 0.5hr off cycle for 1000 hrs.			±(5%+0.05 Ω)	
Soldering Heat Resistance	350°C for 3.5 secs.			±(2%+0.05 Ω)	
ppm / °C Temp. Coeff.	T.C. TYPE	±450	-150~-700	-150~-1000	-150~-1300
		<47K Ω	51KΩ~100KΩ	110KΩ~330KΩ	Over 360kΩ
		<100KΩ	110KΩ~1MΩ	1.1MΩ~2.2MΩ	Over 2.4MΩ

*RCWV" Rated Continuous Working Voltage

