



**HESTORE.HU**

elektronikai alkatrész áruház

**EN:** This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).

datasheet for VQ 30  
 article number: 930061100



product description:	order number: 930 061-100
<b>description:</b>	Fully mating connector, shatter-proof, flexible insulated sleeve with transverse hole. The tapering sleeve end also serves as kinking protection for the lead. Solder connection up to maximum cable cross-section of 2.5 mm <sup>2</sup> . Nickel-plated brass contact material.
<b>typ:</b>	VQ 30 schwarz/black
<b>system:</b>	4mm system
<b>order number:</b>	930 061-100
<b>color</b>	●
<b>other color versions:</b>	●●●●●
technical data	
<b>measurement category acc. to IEC 61010:</b>	CAT I
<b>pin dimensions</b>	4 mm
<b>type of contact:</b>	pin (spring loaded)
<b>type of termination:</b>	solder
<b>rated voltage:</b>	30 VAC / 60 VDC
<b>rated current:</b> <a href="#">Please consider derating curve!</a>	30 A
<b>contact resistance:</b>	3 mOhm
material	
<b>contact material:</b>	brass
<b>contact surface material:</b>	nickel
<b>housing material:</b>	PVC - P
environmental conditions:	
<b>temperature range:</b>	-25 °C to +70 °C
drawing	
	