




**HESTORE.HU**

elektronikai alkatrész áruház

**EN:** This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at [www.hestore.hu](http://www.hestore.hu).

# R13-66



Rating	
16A 125V AC	1/3HP 125V AC
10A 250V AC	1/2HP 250V AC
Contact resistance	
50mΩ Max	
Insulation resistance	
DC 500V 100MΩ Min	
Dielectric strength	
AC 1500V 1 minute	
Cut-out	
X	Y

## FEATURES

- \* MATERIAL: Frame is nylon (UL flame: 94V-2). Terminals are silver plated brass.
- \* Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- \* Snap-in mounting, easy to install switch into panel.
- \* Waterproof cover is optional.
- \* The only difference between R13-66B and R13-66B6 is the rocker style.



act	X	Y
0.75-1.25	18.0±1	13.0±1
1.25-2	18.4±1	13.0±1
2-3	18.8±1	13.0±1

### Cut-out for X8 ROCKER

act	X	Y
0.75-1.25	18.4±1	13.0±1
1.5-2.5	18.8±1	13.0±1



## Ordering number instruction


R13-66 -

### FUNCTION


#### Different button (按鈕不同)



#### Illuminated / Different button (帶燈/按鈕不同)



#### Momentary / Illuminated / Different button (彈跳/帶燈/按鈕不同)



#### Different position / Different button (動作特性不同/按鈕不同)




#### Momentary / Different button (彈跳/按鈕不同)



#### Independent circuit / Different button (獨立通路/按鈕不同)



#### Waterproof (防水)



### TERMINAL

0 2	187° SQ
0 5	SO
0 9	PC
1 0	PC ANGLE
1 2	SO

### ROCKER

A/B/BF/C/D/E/F	G/H/I
B, BF transparent	
A5	
B, BF transparent	
B2/B2F	
L/B4/BF4	
AP/CP/DP/HP/IP	
B6/B6F	
B6, B6F transparent	
A8/B8/B8F/C8	F8