




HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Data Sheet



Type Number 24276
Designation IEC LR 44
System Manganese Dioxide /
 Zinc / KOH - Electrolyte

Nominal Voltage 1,5 V
Typical Capacity C 155 mAh
 Load 5.6 kOhm, at 20°C down to 0.9 V

Weight (approx.) 2,0 g
Volume 0,51 ccm
Coding..... Date of Manufacturing
 Month/Year

Temperature Ranges

	min	max.
Storage	-10°C	65°C
Discharge	-10°C	65°C

Dimensions

	min	max.
Diameter (Ø)	11,25	11,6
Height (A/B)	5,0	5,4

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	0.9 V
Continuous 24h/d,7d/w Current [µA]:	5600 Ω	Time: Capacity [mAh]: Energy [mWh]:	680 h 155 203

* Contact VARTA if the application is intended to be outside the range of -10°C to +65°C.

*Information and contents in this data sheet are for reference purpose only.
 They do not constitute any warranty or representation and are subject to change without notice.
 For most current information and further details, please contact your VARTA representative.*