



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.




LED ALUMINUM MODULE

OF-ALU4FXW WHITE




ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DISCHARGE
SENSITIVE
DEVICES



Features

- 37MMX32MM WATERPROOF LED MODULES (4-LED) .
- MODULE THICKNESS : 6.5MM.
- WORKING VOLTAGE : 12V DC.
- WORKING CURRENT: 40MA.
- LED VIEW ANGLE(2 θ 1/2):80°.
- PACKAGE: 200PCS / BAG.

Package Dimensions :



Notes:

1. All dimension units are millimeters.
2. All dimension tolerance is ± 1 mm unless otherwise noted.



LED ALUMINUM MODULE

Absolute Maximum Rating at TA=25°C

Parameter	Symbol	Absolute Maximum Rating	Unit
Forward Current	IF	40	mA
Power Dissipation	PD	0,48	W
Electrostatic discharge	ESD	800	V
Operating Temperature	Tstg	-25 ~ +60	°C
Storage Temperature	Tstg	- 40 ~ + 80	°C

Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	Condition	Min	Typ	Unit
Forward Voltage DC	VF	IF=40mA		12	V
Dominant Wavelength	λ D	IF=40mA			nm
Luminous flux	ϕ V	IF=40mA		18	lm
Recommend Forward Current	IF(rec)	IF=40mA		40	mA

Notes:Tolerance of measurement of luminous intensity \pm 15%.

Package means



APPLICATIONS

- SLIM DESIGN FOR NARROW AND COMPACT LED SIGNAGES.
- WATERPROOF FOR OUTDOOR ADVERTISING SIGNS CHANNEL-LETTER , EFFECTIVE CONTOURING , OUTDOOR WATERPROOF LED LIGHTING PROJECTS , ETC.