

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.



## **Installation Manual**

 Type: Enclosed Type Switching Power Supply (Families: G3, NE, LRS, SE, PFC, HSP, SPV, USP, RST, G5, MSP)

### Introduction

Enclosed type switching power supplies possess a metal or plastic case for covering their internal PCB and will be installed inside the case of the end system. Mean Well's enclosed type power supplies include 2 different groups of power supplies, with built-in fan and without built-in fan, depending on their rated power or design concept.

#### Installation

- (1) Before any installation or maintenance work, please disconnect your system from the utility. Ensure that it can't be re-connected inadvertently!
- (2) Keep enough insulation distance between mounting screws and internal components of power supplies. Please refer to case drawing on specifications to receive the maximum length of mounting screw.
- (3) Mounting orientations other than standard orientation or operate under high ambient temperature may increase the internal component temperature and will require a de-rating in output current. Please refer to the specification sheets to receive the optimum mounting position and information about the de-rating curve.
- (4) Fans and ventilation holes must be kept free from any obstructions. Also a 10-15 cm clearance must be kept when the adjacent device is a heat source.
- (5) Recommended wires are shown as below.

AWG	18	16	14	12	10	8
Rated Current of Equipment (Amp)	6A	6-10A	10-16A	16-25A	25-32A	32-40A
Cross-section of Lead(mm <sup>2</sup> )	0.75	1.00	1.5	2.5	4	6

Note: Current each wire carries should be de-rated to 80% of the current suggested above when using 5 or more wires connected to the unit.

Make sure that all strands of each stranded wire enter the terminal connection and the screw terminals are securely fixed to prevent poor contact.

(6) For other information about the products, please refer to www.meanwell.com for details.

## Warning / Caution !!

- (1) Risk of electrical shock and energy hazard. All failure should be examined by a qualified technician. Please do not remove the case of the power supply by yourself!
- (2) Please do not install power supplies in places with high moisture or near the water.
- (3) Please do not install power supplies in places with high ambient temperature or near fire source. The maximum ambient temperature please refer to their specifications.
- (4) Output current and output wattage must not exceed the rated values on specifications.
- (5) The ground(FG) must be connected to earth ground.
- (6) All MW's PSUs are designed in accordance with EMC regulations and the related test reports are available by request. Since they are belong to component power supplies and will be installed inside system enclosure, when they are integrated into a system, the EMC characteristics of the end system must be re-verified again.



# **Installation Manual**

## **Manufacturer**:

MEAN WELL ENTERPRISES Co., LTD. No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

Tel: +886-2-2299-6100 Web: www.meanwell.com

## **Branch Office:**

#### China

MEAN WELL (GUANGZHOU) ENTERPRISES Co., LTD. 2F, A Building, Yuean Industry Park, Huangcun, Dongpu Yown, Tianhe District, Gungzhou, China Post Code:510660

Tel: +86-20-2887-1200

Web: www.meanwell.com.cn

#### U.S.A.

MEAN WELL USA, INC. 44030 Fremont Blvd., Fremont, CA 94538, U.S.A.

Tel: +1-510-683-8886

Web: www.meanwellusa.com

#### Europe

MEAN WELL EUROPE B.V. Langs de Werf 8, 1185XT Amstelveen, The Netherlands

Tel: +31-20-758-6000 Web: www.meanwell.eu