



HESTORE.HU

elektronikai alkatrész áruház

EN: This Datasheet is presented by the manufacturer.

Please visit our website for pricing and availability at www.hestore.hu.

Microphone cables



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: Compact PE
 Core colour: Transparent
 Shield: Braided covering 90%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C129	1	1 x 0,35 (22 AWG)	11x0,20	3,0	5,2	100	B	3,5

nightly blue®



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
60		89
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



Applications:
Unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: Compact PE
 Core colour: Transparent
 Shield: Braided covering 100%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colour: Transparent

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C195	1	1 x 0,50 (20 AWG)	16x0,20	2,1	6,0	100	B	4,2

nightly blue®



Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
45		130
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70



Applications:
Professional unbalanced microphone cable and for sound reproduction.

Characteristics:
 Conductor: O.F.C. red copper
 Cond. Insulation: PVC
 Core colour: White
 Inner cotton: Braided covering 95%
 Shield: Braided covering 95%
 O.F.C. tinned copper
 Sheath: PVC
 Sheath colours: Red, Blue, Yellow, Green

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C209	1	1 x 0,75 (18 AWG)	24x0,20	3,0	6,2	100	B	5,3

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
30		236
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70